
PW2

Widebody Front-Loading Warewasher
W 1235mm x D 860mm x H 1790mm



Washtech warewashers are built to improve the efficiency of operations washing oversized and/or heavily soiled items, from bakeries to production kitchens, supermarkets to hospitals. This is achieved with a continuous and consistent wash process throughout the day that is easy on your staff. With highly efficient water consumption rates, they are also light on the environment and operating costs.

The PW2 is a powerful, highly durable, simple-to-use and easy-to-maintain front-loading warewasher. It features Washtech hybrid controls which combine IP67 stainless switches, tried-and-tested switchgear, with a customisable electronic timer. Built with a large wash chamber and counterbalanced split door, the PW2 is ideal for washing bins, crates, bowls and other oversized items.

Since 1981 Washtech dishwashers have been constructed from heavy-duty stainless steel, and are engineered specifically for Australian conditions and regulations. Backed by the most extensive service network and spare parts inventory in the region, your Washtech PW2 will not let you down.

Standard Features
- Versatile 2, 4 and 6 minute wash cycles
- Large internal wash chamber with useable area of W 1100mm x D 650mm x H 750mm
- Low hot water consumption of 4.0 litres per cycle
- Washtech hybrid controls
- Easy installation supplied with:
    - Water supply hose
    - Detergent and rinse aid pumps with injector lines
- Internal upper rail with optional and adjustable tines suited for hanging ladles, whisks and/or washing up to 20 baking or GN trays (up to 40mm deep) per cycle
- High powered dual-pump wash system
- Suitable for connection to low inlet water temperature and/or pressure (break tank and rinse pump fitted)
- Heavy-duty stainless steel construction and wash manifold
- Robust stainless steel wash and rinse arms with precision stainless steel jets
- Double heavy-duty stainless steel filtration system including dual scrap trays and separate wash inlet filter
- Wash chamber easily accessible via insulated counter-sprung split door
- Watermark approved backflow prevention
- Moffat's comprehensive 5-2-1 Warranty



Includes:
- 1 x 500mm dish rack (600 70028)
- 1 x 500mm cup rack (600 70029)
- 1 x 435mm cup cover (K0452)
- 1 x cutlery basket (C660508)
- 1 x potwasher rack grid (824 30001)
- 1 x hanging rail with adjustable tines (824 10228)



15YR PARTS AVAILABILITY
WaterMark WMT5101 Cert 08603 SAI GLOBAL
5·2·1 WARRANTY

WASHTECH

PW2

MOFFAT

moffat.com.au
washtech.com.au

Moffat Pty Limited

VIC/TAS/SA
70 Springvale Road
Mulgrave, Victoria 3170
Telephone 03-9518 3888
Fax 03-9518 3833
vsales@moffat.com.au

NSW
Telephone 02-8833 4111
nswsales@moffat.com.au


QLD
Telephone 07-3630 8600
qldsales@moffat.com.au

WA
Telephone 08-9413 2400
wasales@moffat.com.au

In line with policy to continually develop and improve its products, Washtech reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd

Version: WPW20020 2103



A – Hot Water*

Temperature	65°C
Connection	3/4” male; hose supplied
Pressure	100-350kPa
Flow	10 litres per min
Quality	Potable - refer table
Backflow Prevention	AVB
Consumption	4.0 litres per cycle

B – Waste

Connection	1.5” BSP male
Line	2.0” / 50mm minimum

C – Electrical	**V**	**Hz**	**A/phase**	**Max kW**
Three Phase	400	50	30	19.50
Three Phase	400	50	20	12.00

Dimensions	**Machine**	**Packed**
Width (mm)	1235	1310
Depth (mm)	860	945
Height (mm)	1790	1830
Weight (kg)	220	276
Volume (m^3)		2.18

Water Quality	**Min**	**Max**
pH	7	8
Hardness (ppm)	20	100
Cl-		100
SO_4		400
Fe		0.1
Mn		0.5
Cu		0.05
Cl_2		0.1

Isolating switch must be within 1m of, and not directly behind the machine.

* Suitable for connection to cold inlet water. For optimal productivity, use hot inlet water.

Refer to operator manual for installation instructions.

ISO 9001 BUREAU VERITAS Certification

an Ali Group Company
The Spirit of Excellence

24:7 Service Support

WaterMark WMTS101 Cert 08603 SAI GLOBAL

5·2·1 WARRANTY